

STAINOX N PICKLING PASTE

Chloride-free pickling paste for the cleaning of weld seams on stainless steel & other oxidising acid resistant metals. Please read the relevant MSDS for this product before use.

INSTRUCTIONS

1. Stir before use to obtain a smooth paste using a plastic or wood rod or spatula.
2. Apply to a cold surface (5-30 C) with an acid resistant brush.
3. Leave the paste on the job as follows:
 - Stainless steel 15-60 min.
 - Other acid resist. metals: 5-20 min.
4. Rinse thoroughly with water to remove all residue. Rinsing water should be neutralised to pH 7 by using lime before disposal. A plastic or stainless steel brush may also be used to aid residue removal.

1 Litre

STAINOX N

PICKLING PASTE

STAINLESS TRADING (PTY) LTD
TEL: (011) 822 1303

UN No. 3264



- This product contains hydrofluoric & nitric acid.
- It may cause severe chemical burns.
- Do not allow contact with skin or eyes.
- This product is toxic, do not swallow.
- Wear suitable personal protective clothing including acid resistant gloves & eye protection.
- In case of contact with skin or eyes, rinse immediately with water & seek medical advise. (Show label if possible).
- Do not breathe the fumes.
- Avoid release to the environment.
- Remove all contaminated clothing immediately.
- Wear suitable respiratory equipment in case of insufficient ventilation.